



NB. Clearance Factor Measurement x to y is taken from wall to cooker

Screen is fixed to the wall

The following are minimum clearances to Combustible Surfaces	B1 Below cooking surface	B2 Above cooking surface	A Rear Wall		D1 Below cooking surface	D2 Above cooking surface
			With upstand	No upstand		
Unprotected walls without upstand	160mm	425mm	425mm		25mm	75mm
Unprotected walls with upstand	160mm	425mm	100mm		25mm	75mm
Screening sheet metal of any type 0.5mm or thicker spaced 25mm from wall	48mm	128mm	30mm	128mm	25mm	30mm
Screening 12mm Eterpan LD Board spaced 25mm from wall	47mm	124mm	29mm	124mm	N/A	N/A

Other screening materials are available and clearance factors can be calculated to AS/NZS2918:2001. Please ask your retailer or contact Wagener Stoves if you need further advice.

NB The Wagener Fairburn will fit into most existing brick alcoves which have previously accommodated an older style wood or coal range. (ie brick with 25mm air space behind). Leg height can be modified to suit if required.

Floor Protector (Ash Hearth): Shall extend under appliance and forward of the fire box opening 300mm, and extend 200mm to the side of the firebox opening (ie 120mm from side of end panel).

Wagener Fairburn Dimensions

Flue Size	150mm		
Oven Internal Dimensions			
Width	410mm		
Height	360mm		
Depth	465mm		
Oven Wire Racks	4 Heights		
Firebox Internal Dimensions			
Width	250mm		
Height	280mm		
Depth	360mm		
Wetback (Rear outlet)	Single	Dble	Boiler
Estimate on Hardwood	2kw	3.5kw	5.5kw
Estimate on Softwood	2.5kw	4.5kw	7kw
Estimated Heat Output	16kw		
Estimated Weight	300kg		

